



The Forum CONFER III allows you to conference customers, managers and team members and keep your business running smoothly. You need a partner who is as dependable as our technology.



The CONFER III is the most durable voice conference system on the market, with the most competitive price in the industry and the latest in DSP technology and design.

Modularity, interoperability, flawless sound clarity and long-term superior service meet in an affordable, easy-to-use, plug-and-play bridge:

- \* Host your own conference calls and save hundreds or thousands of dollars per month over your current conference service.
- \* Upgrade your existing or outgrown conference hardware.
- \* Bring your conference call meetings in-house for enhanced security.
- \* Implement a smooth transition to our more affordable conference call solutions.
- \* Enhance your productivity and bottomline for management and shareholder payback.

Since 1991, thousands of major corporations, telecom/IT managers, and emergency response agencies choose and recommend Forum conference technology. Forum Communication's support and training programs keep your system at peak performance.

The CONFER III interfaces with virtually ANY PBX or Key System in today's evolving multi-vendor environments. Upgrades and feature enhancements are designed for instant and remote installation.

Remote Administrative options let you bundle the Confer III enhanced conference control, remote configuration and management functions. CONFerview software gives you real-time display and control via GUI Interface direct connect or Modem.



**Forum Communications**  
**When you can't meet face to face**

## SPECIFICATIONS

### Features

Meet-Me conferencing  
 Automatic echo cancellation for plug and play installation. No set-up.  
 Full-duplex conversation using patented algorithm  
 Automatic gain adjust for high quality conversation  
 Entry/exit tones  
 Lockout of unused ports  
 Versatile configurations for multiple conferences  
 Self mute/unmute

### Options

Voice Prompts	Authorization Codes
Custom Greetings	Remote Administrative Options
Dial Out	Remote Audio Monitoring
Virtual Gavel	Blast Dial
Headcount	ConferView

### Interface

FCC Part G8 compliance  
 2-wire loop-start/ground-start lines  
 Optional 2-wire audio, 4-wire audio  
 Line interfaces: RJ-11 jacks and/or 50-pin Amphenol-Type connectors  
 Recorder output jack, optional audio-input jack: subminiature  
 Control/Monitor/Remote Administrative Port  
 Optional RS-232 interface for control and monitoring functions  
 Ring-detection joins port to conference with entry tone  
 Disconnect Supervision: Loop-current interrupt, dial tone/ reorder tone detection, A-tone, D-tone

### Capacity

Card Cage - Implemented in multiples of 8 lines, up to 72 lines  
 Card Cage is recommended for maximum management capabilities  
 Unit - 8 line unit

### Physical

CARD CAGE	Size: 16"H x 19"W x 12"D Weight: 11.5 lbs with power supply, plus 1.75 lbs per 8-port card Wall or rack mount Capacity: Up to 9 Confer III Cards for up to 72 ports
UNIT	Size: 19.5"H x 9"W x 3"D Weight: 10 lbs Capacity : 8 ports

### Power

115/220 VAC 50-60 hz, 130 watts max. (card cage), 25 watts nominal (unit)

### Environmental

Operating Ambient: 50 C to 500 C, 10 percent RH to 80 percent RH, non-condensing

